

## Ref. 04073 Automatic sanitizer dispenser with thermometer function

Nº	Features	Sub option	Specification	Remark
1	Power	DC	6V/1A	optional
2		current	Working current <220UA	DC6V, with pump testing difference load, difference current.
3			Maximum working current:1.35A	
4			Pump working Current :0.53A	
5		Battery	4 pcs C type battery 1.5V*4	<3.7V low-voltage warning red light flash 1 time in every 4 seconds <3.4V, low-voltage protection mode the red light will flash 10 times to enter the low-power consumption mode.
6		Lifespan	Testing with "Nanfu" and "555" brand battery.	
7	Temperature optional	°C/°F	Celsius or Fahrenheit degree options	The button is placed on the right side of the display.
8	LED indicator	Green/Red	Regular working color:Green light flash in every 4s	The indicator light is placed on the left side of the display.
9			low-voltage warning <3.7V, red led light flash one time in 4s	
10			low-voltage protection<3.4V,red led light flash 10 times	
11			Hand sensor ,motor working,the led turn on green	
12			After the motor working one time,hands still under the dispenser ,the red light flash	
13	Alarm and backlight	Alarm	≥60dB	
14		>42.2°C	3times warning	red backlight.
15		38.2~42.2°C	3times warning	red backlight.
16		37.4~38.0°C	3times warning	pink backlight.
17		<32°C	1times warning	blue backlight.

18	LCD	digital LCD display		
19		Screen out protection	10S	
20	Temperature display	<32.0°C	blue back light, display "Lo"	Temperature display ranges between 32.0-42.2°C
21		37.4~38.0°C	Pink back light	
22		38.1~42.2°C	red back light	
23		>42.2°C	red back light ,display "HI"	
24	Sensor distance	Hands sensor	8-12cm	
25	Using Temperature	Environment Temperature	-5~40°C	
26	Using humidity	Environment humidity	15~85%RH	
27	Certifications	CE RHOS FCC		