

# PAPER TOWEL DISPENSER

# SURFACE MOUNTED STEEL WHITE EPOXY

# Code: DT2106

275mm (10 3/4"

179mm (7"

S

S

S

330mm [13\*]

## **General description**

Paper towel dispenser, surface mounted, steel white epoxy coated. Manual dispenser.

Robust and vandal-resistant.

Suitable for high traffic facilities.

Model suitable for public use.

It generally goes along with a soap dispenser and paper waste receptacle steel white epoxy, complemented by a warm air hand dryer.

Rear base plate provides multiple mounting slots.

Front opening lid by using a provided mediclinics key.

# **Components and Materials**

Steel white epoxy coated perfectly welded body, 0,8mm thick. It is mounted on the wall by means of 4 screws with their corresponding Ø6mm wall plugs (screws and wall plugs provided). The support of the screws in the back of the appliance are acting as an antimoisture support, as well as allowing an easy adjustment to the wall. The slots inside of the body avoid the screws damaging the paper towels. The opening presents edged borders in order to avoid tearing of paper towels.

Steel white epoxy coated, seamless one-piece lid, 0,8mm thick. Fixed to the body by means of 2 rivets. It includes a lock with standard mediclinics key, that allows swinging down of lid for replenishment.

A frontal window indicates refill time.

Dimensions	330x275x130mm	Towels	100x260 mm max.		
Weight (empty)	1,80 Kg	C-fold towel capacity	400 u	275mm [10 3/4"]	
Recommended installation height	130-160 cm to lower point	Multifold (Z-fold) towels capacity	600 u	30mm/5 1/81	
Recommended installation height for handicapped	85-120 cm to lower point			Dim ± 49	

## Operation

Pull the towel until it detaches from the appliance. Repeat the action, at your own convenience.

## **Certificates & Qualifications**

ISO 9001:2008.

## Specification

Surface mounted paper towel dispenser, shall be made of steel white epoxy coated. Unit shall dispenser either 400 C-fold or 600 multifold (Z-fold) towels. The body shall be made of steel white epoxy coated, 0,8mm. The support of the screws should act as an anti-moisture support, as well as slots to avoid the screws damaging the paper towels and permit the easy adjustment to the wall. It should be suitable to be mounted on the wall by means of 4 screws with their corresponding Ø6mm wall plugs (screws and wall plugs provided). The opening should present edged borders in order to avoid tearing of paper towels. The lid should be made of steel white epoxy coated one-piece seamless, 0,8mm and fixed to the body by means of 2 rivets. It includes a lock with standard mediclinics key, that allows swinging down of lid for replenishment. The appliance should have a frontal window to indicate refill time. Overall dimensions shall be 330x275x130mm.

Paper towel dispenser shall be model DT2106, steel white epoxy coated, of Mediclinics