

TASKI® swingo® XP

Stand on automatic scrubber drier



Key Features

- ▶ Greatly increased productivity
- ▶ Highest cleaning results
- ▶ Immediately dry floors
- ▶ Reduced water and energy consumption

Greatly increased productivity

- ▶ The new stand-on concept with sensor steering combines excellent manoeuvrability with speed for faster cleaning. A highly efficient water management system reduces the number of time-consuming tank filling stops.

Highest cleaning results

- ▶ The new scrubbing unit with micro-rotating movement offers high level cleaning results, while saving up to 50% of the cleaning solution versus conventional rotary or cylindrical brush systems.

Immediately dry floors

- ▶ The excellent drying result (due to the W-shaped squeegee) allows use of the machine at any time of the day, while reducing the potential risk of slip-fall accidents caused by wet floors.

Reduced water and energy consumption

- ▶ Due to the speed dependant Cleaning solution dosing (CSD system) the environmentally-friendly machine leads to more efficient use of natural resources.
-

TASKI swingo XP Specifications

Technical Data

Description		Description	
Theoretical performance	4500 m ² /h	Machine weight ready for use (w/o driver)	410 kg
Working width	75 cm	Dimensions (L x W x H)	119x95x126 cm
Squeegee width	95 cm	Door pass through width (w/o squeegee)	85 cm
Solution tank-bag system	105 l	Brush system	45 x 15 cm
Recovery tank	105 l	Micro-rotation speed of brushes	550 rpm
Rated voltage	24 V	Brush pressure min-max	0.25-0.5 N/cm ²
Nominal consumption	1,200 W	Cleaning speed	6 km/h
Battery capacity (max)	195 Ah/C5	Sound level	65 dB(A)
Battery run time	3.5 h		
Machine weight net	180 kg		

TASKI swingo XP

Model	SKU Number
TASKI swingo XP	
TASKI swingo XP BMS	

Accessories

Description	SKU Number	Description	SKU Number
Scrubbing brush Nylon 450 mm	7514650	Filling hose with universal coupling	8502830
Pad drive harpoon grip 450 mm	7514648	TASKI JFit kit for swingo XP	7516242
Scrubbing brush hard 450mm	7515725		
Scrubbing brush abrasive 450mm	7515726		

Description of Features

BMS (Battery Management System): An internal monitoring system prevents deep discharging of the batteries. LED Battery display allows the operator to visually check condition of battery charge.

CSD (Cleaning Solution Dosing): The CSD system allows for a speed-dependent supply of cleaning solution. This feature ensures that the amount of solution dosed onto the floor is always constant—no matter how fast the machine is operating. The result? No puddles in curves and turns as well as a 30-50 percent saving in cleaning solution, leading to significantly increased productivity of the machine.

Micro rotating scrub deck: Combines the best attributes of rotary and cylindrical cleaning all in one patented scrubbing platform. No need to choose one or the other.

Patented squeegee: The unique “W” shape with dual pickup hoses continuously self-adjusts to the flooring surfaces and delivers a dry floor without “trail mopping.” Easy on/off squeegee.